



# Model 1601 Heliport Recessed Flushlight

## Applications

Our omnidirectional incandescent Heliport Recessed Flushlight is designed to be almost flush with the ground surface and is used in a variety of helipad lighting applications.

- Perimeter Lights: Outlines the heliport landing area
- Landing Direction Lights: Indicates the preferred approach
- Threshold Lights: Marks the front edge of the heliport

## Features

- Flush Mounted
  - Recessed, almost flush with the surface
  - Permits the obstruction-free movement of equipment and personnel
- Optically Designed Lens
  - Omnidirectional beam assists the pilot in maintaining correct glide path
  - Lens made of non-breakable plastic (Lexan)
- Heavy Construction
  - Housed in a heavy, machined, cast aluminum enclosure
  - Rugged cast aluminum guard fits precisely to protect the lens and optics without obstructing emissions
  - Lens guard with 6 spokes available
- Easily Installed
  - May be recessed in soil or solid aggregate or bolted to the edge of an elevated heliport
- Weatherproof
  - Entire fixture is fully machined and double gasketed to make it weathertight

## Specifications

- Case: Cast Aluminum
- Lens: Lexan
- Light Colors: Green, Yellow, Blue, Red or Clear
- Lamp: 60 Watt Incandescent
- Lens Guard: Cast Aluminum, 3 Spokes (standard), 6 Spokes (optional)
- Power: 120 VAC, or other
- Dimensions: Flange Square: 8"; Depth: 5.25"; Bottom Diameter: 6"
- Weight: 8 lb.
- Finish: Polyester Powder Coating, Orange



## LED Retrofit Kit

Our LED Retrofit Kit is made to replace the standard incandescent lamp. It only consumes 8 Watts (LED lamp) compared to 60 Watts (standard lamp). This provides big savings in power consumption along with a reduction in heat generation. This long-lasting lamp will also help reduce the frequency of lamp changes. The aqua green color of the lamp does not affect pilots with night vision goggles.



## Features

- 3 year LED lamp module limited warranty
- Easy installation using existing socket
- LED operating life: 100,000+ hours (10+ years)
- Solid-state, fast turn on, no power surge
- High shock / vibration resistant
- Major power savings
- Standard voltage 120 VAC, others available (240 VAC)
- Major reduction in heat generation